

Product: 60 Density Hard Glue Lamination Foam

Product Code: FV-In Rolls-60HG

60 Density Hard Glue Lamination foam is a bit close cell, high-density polyether-based foam offering high hardness & elongation compared to normal grade or low-density foams. High density & hardness enable these foams to offer better support and firmness at the place of application.

Our International Exposure with Hard Foams: India, China, Turkey & Bangladesh.

PARAMETERS	VALUES
Density (Kg/m3)	60 (+/-)2
Tensile Strength (Kgf/cm2)	Greater than 2
Elongation (%)	Greater than 100
Hardness Value (IFD) Kg/323 cm2 at 50% Compression	80 (+/- 4)
Resilience (%)	Greater than 25

Advantages

- A. Extra harness, firmness, and support compared to Standard foam grades.
- B. Flexible, allowing breathability and air circulation.
- C. Offer long shelf life at the place of application

Specifications

Density: 60 Kg/m3.

Cell Structure: Fine and Regular.

Common Width: 1.5 meters

Common Thickness: 2.8, 3.2, 3.8 mm.

Common Color: Black.

Supply: No supply constraint.

Packaging: Each Roll is in an HM plastic sheet and then in an HDPE bag.

Preferred Lamination Process: Glue.

Delivery: Within 5 days once the order is confirmed.

Application

Footwear, Automotive Industry, Carpet Underlay, Saddles, Medical Products, and applications where extra foam support and firmness are required.



Foam Processing in Rolls



Hard Foam in Rolls



Hard Foam Products

Why Foam Villa

- Expert Consultancy
- Global Tie-ups
- Competitive Pricing
- Quality Products & Services
- On-Time Delivery
- Business Transparency

Contact Us

☎ +91-9958535980

✉ info@foamvilla.com

🌐 www.foamvilla.com

📍 Delhi/NCR Region, India.

Follow Us At:-

